



525W - 550W BF 182 Mono PERC 10BB Half Cut 72x2

Design Parameters		Related Standards / Certificate		Drawing	
Product Model	PS-MO-HC-XXX	TS EN 61215-1 / 20.03.2017			
Cell Type	BF 182 Mono PERC 10BB	TS EN 61730-2 / 19.11.2018			
Number of Cells	Half Cut 72x2	TS EN 61215-2 / 18.12.2017			
Glass	3,2 mm	TS EN IEC 61730-1 / 19.11.2018			
Back Cover	PET White	TS EN 61730-1 / 31.01.2008			
Frame	Anodized Aluminium Alloy	TS EN 61215-1-1 / 09.12.2016			
Output Cables	1200-1100-300 mm 1x4,0 mm2				
Junction Box	IP68 Rated				
Packing					
Weight	27,5 kg				
Dimension	2279mm-1134mm / 35X35 Gray				
Pieces	32 pcs/pallet				
Truck	704 pcs/ Truck				

Electrical Characteristics													
Power Class	550		545		540		535		530		525		
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	
Module Efficiency	21,26%		20,99%		20,83%		20,63%		20,19%		20,36%		
Maximum Power (Pmax)	550	408,32	545	404,61	540	400,90	535	397,18	530	393,47	525	389,76	
Maximum Power Voltage (Vmp)	41,50	35,76	41,30	35,59	41,10	35,41	40,90	35,24	40,85	35,20	40,82	35,17	
Maximum Power Current (Imp)	13,25	11,42	13,20	11,37	13,14	11,32	13,08	11,27	12,97	11,18	12,86	11,08	
Open Circuit Voltage (Voc)	50,10	43,17	49,90	43,00	49,70	42,82	49,50	42,65	49,45	42,61	49,40	42,56	
Short Circuit Current (Isc)	13,99	12,05	13,96	12,03	13,90	11,98	13,84	11,92	13,74	11,84	13,64	11,75	

*Standart Test Conditions (STC): irradiance 1000W/ m2 ,A.M 1.5, cell temperature 25 °C - "Nominal Operating Cell Temperature (NOCT): irradiance 800W/ m2 , A.M 1.5 , Ambient temperature 20 °C , Wind 1 m/s" . Diagrams for STC.

Temperature Ratings			Diagrams		
Temperature Coefficient of Pmax	-0,36% (°C)	-0,36% (°C)			
Temperature Coefficient of Voc	-0,30% (°C)	-0,30% (°C)			
Temperature Coefficient of Isc	0,05% (°C)	0,05% (°C)			
Operating Temperature (°C)	-40(°C) ~+85 (°C)	-40(°C) ~+85 (°C)			
Electrical Limits					
Maximum System Voltage	1500 VDC (IEC & UL)	1500 VDC (IEC & UL)			
Maximum Series Fuse Rating	25 A	25 A			
Power Tolerance	0 ~ +3%	0 ~ +3%			
Mechanical Limits					
Front Side Static Design Loading	3600 Pa	3600 Pa			
Back Side Static Design Loading	1600 Pa	1600 Pa			
Hailstone	d: 25 mm, 23 m/s	d: 25 mm, 23 m/s			